

Package: CREAM (via r-universe)

September 13, 2024

Type Package

Title Clustering of Genomic Regions Analysis Method

Version 1.1.1

Date 2018-05-30

Description Provides a new method for identification of clusters of genomic regions within chromosomes. Primarily, it is used for calling clusters of cis-regulatory elements (COREs). 'CREAM' uses genome-wide maps of genomic regions in the tissue or cell type of interest, such as those generated from chromatin-based assays including DNaseI, ATAC or ChIP-Seq. 'CREAM' considers proximity of the elements within chromosomes of a given sample to identify COREs in the following steps: 1) It identifies window size or the maximum allowed distance between the elements within each CORE, 2) It identifies number of elements which should be clustered as a CORE, 3) It calls COREs, 4) It filters the COREs with lowest order which does not pass the threshold considered in the approach.

License GPL (>= 3)

Imports stats, utils

Depends R (>= 3.3)

URL <https://github.com/bhklab/CREAM>

Suggests testthat

RoxygenNote 6.0.1

Roxygen list(markdown = TRUE)

LazyData true

biocViews PeakDetection, FunctionalPrediction, BiomedicalInformatics, Clustering

BugReports <https://github.com/bhklab/CREAM/issues>

Encoding UTF-8

Repository <https://bhklab.r-universe.dev>

RemoteUrl <https://github.com/bhklab/cream>

RemoteRef HEAD

RemoteSha 718264747fd4f6886ffcf260d70fb2b2892b04d

Contents

CREAM	2
ElementRecog	3
PeakMinFilt	4
WindowSizeRecog	4
WindowVec	5

Index	7
--------------	----------

CREAM	<i>CREAM is the main function for CORE identification</i>
-------	---

Description

CREAM is the main function for CORE identification

Usage

```
CREAM(in_path, WScutoff = 1.5, MinLength = 1000, peakNumMin = 2)
```

Arguments

<code>in_path</code>	Path to the input file (The file including the functional regions) Note. You have to make sure that there is no overlapping regions within the input file
<code>WScutoff</code>	Threshold used to identify WS within distribution of maximum distance between peaks for each order of CORE
<code>MinLength</code>	Criteria for the minimum number of functional regions in the input file
<code>peakNumMin</code>	Minimum number of peaks for CORE identification

Value

Bed file including the identified COREs

Examples

```
CREAM(system.file("extdata", "A549_Ch21.bed", package = "CREAM"),
MinLength = 1000, peakNumMin = 2)
```

ElementRecog

ElementRecog is a function to identify COREs

Description

ElementRecog is a function to identify COREs

Usage

```
ElementRecog(InputData, windowSize_Vec, peakNumMax, peakNumMin)
```

Arguments

InputData	The input data as a table including chromosome regions in which the first column is chromosome annotation, and second and third columns are start and ending positions.
windowSize_Vec	Vector of window sizes ordered based on order of CORE
peakNumMax	Maximum order of COREs (e.g. maximum number of peaks within COREs)
peakNumMin	Minimum order of COREs (e.g. minimum number of peaks within COREs)

Value

Identified COREs for the given input regions

Examples

```
InputData <- read.table(system.file("extdata", "A549_Chr21.bed",
package = "CREAM"), sep="\t")
colnames(InputData) <- c("chr", "start", "end")
MinLength <- 1000
if(nrow(InputData) < MinLength){
  stop(paste("Number of functional regions is less than ", MinLength,
  ".", sep = "", collapse = ""))
}
peakNumMin <- 2
WScutoff <- 1.5
WindowVecFinal <- WindowVec(InputData, peakNumMin, WScutoff)
OutputList <- ElementRecog(InputData, WindowVecFinal,
(1+length(WindowVecFinal)), peakNumMin)
```

PeakMinFilt	<i>PeakMinFilt is a function to filter the lowest Order of COREs which distance between functional regions is close to the corresponding Window Size</i>
-------------	--

Description

PeakMinFilt is a function to filter the lowest Order of COREs which distance between functional regions is close to the corresponding Window Size

Usage

```
PeakMinFilt(Clusters_init, WindowVecFinal)
```

Arguments

Clusters_init	Table of indetified COREs before filtration
WindowVecFinal	Vector of window sizes ordered based on order of CORE

Value

Minimum order of COREs

WindowSizeRecog	<i>WindowSizeRecog is a function to specify window size for each order of COREs</i>
-----------------	---

Description

WindowSizeRecog is a function to specify window size for each order of COREs

Usage

```
WindowSizeRecog(InputData, COREorder, WScutoff)
```

Arguments

InputData	The input data as a table including chromosome regions in which the first column is chromosome annotation, and second and third columns are start and ending positions.
COREorder	Order of the COREs which window size has to be determined for.
WScutoff	Threshold used to identify WS within distribution of maximum distance between peaks for each order of CORE

Value

Window size identified for each order of CORE

Examples

```
InputData <- read.table(system.file("extdata", "A549_Chr21.bed",
package = "CREAM"), sep="\t")
colnames(InputData) <- c("chr", "start", "end")
MinLength <- 1000
if(nrow(InputData) < MinLength){
  stop(paste( "Number of functional regions is less than ", MinLength,
  ".", sep = "", collapse = ""))
}
peakNumMin <- 2
WScutoff <- 1.5
WindowSize <- WindowSizeRecog(InputData, peakNumMin, WScutoff)
```

WindowVec	<i>WindowVec is a function to specify window size for each order of COREs</i>
-----------	---

Description

WindowVec is a function to specify window size for each order of COREs

Usage

```
WindowVec(InputData, peakNumMin, WScutoff)
```

Arguments

InputData	The input data as a table including chromosome regions in which the first column is chromosome annotation, and second and third columns are start and ending positions.
peakNumMin	Minimum order of COREs
WScutoff	Threshold used to identify WS within distribution of maximum distance between peaks for each order of CORE

Value

Vector of window sizes from order 2 up to maximum order of COREs

Examples

```
InputData <- read.table(system.file("extdata", "A549_Chr21.bed",
package = "CREAM"), sep="\t")
colnames(InputData) <- c("chr", "start", "end")
MinLength <- 1000
if(nrow(InputData) < MinLength){
  stop(paste( "Number of functional regions is less than ", MinLength,
  ".", sep = "", collapse = ""))
}
peakNumMin <- 2
WScutoff <- 1.5
WindowVecFinal <- WindowVec(InputData, peakNumMin, WScutoff)
```

Index

CREAM, [2](#)

ElementRecog, [3](#)

PeakMinFilt, [4](#)

WindowSizeRecog, [4](#)

WindowVec, [5](#)